

BADU[®] Delta Eco VS



The BADU Delta swimming pool pump has a motor display with intuitive controls, which ensure low energy consumption. It is especially quiet and efficient due to newly configured hydraulics. LED lighting in the transparent lid aids sight inspections. Inset drain plugs avoid risk of breakage. The permanent magnet motor provides efficient energy savings. Can be controlled using the BADU Eco Logic remote control.

The pump is delivered ready for connection with a 5-wire control cable, cable and plug.

Products in the BADU Delta series are only available via specialist retailers. Their high quality and technical demands require specialist knowledge for the planning and installation.

Details

Class: PREMIUM

Installation: Built-in pool

Motor performance in kW (P2): 1,10

Pool equipment: Circulation pumps

Pool type: Innenpool

Strainer basket in mm: ca. 2,2 x 2,2

Strainer capacity in l: ca. 4

Total head H in m WS: 8

Materials used

Impeller: PPE GF 30

Intermediate housing: PP GF 30

Lid: PC, transparent / PA 66 GF 30

Mechanical seal: carbon / ceramic / NBR

Pump casing: PP GF 30

Screws: Edelstahl

Strainer basket: PP

Field of application

Swimming pool water circulation through a filter system. The pump can be installed max. 3 m above or below water level.

Design

Monoblock-type pump with integrated strainer tank. Motor/pump shaft has no contact with the pool water, providing complete electrical separation.

Motors

Special motors on request.

Miscellaneous

Also available in special design. The pumps, as described, can be used for pool water with a salt concentration of up to 0.5%, i.e. 5 g/l. For higher salt concentrations please contact the company SPECK Pumpen.

Downloads

- [3D model](#)
- [Spare parts list](#)
- [Catalogue page](#)
- [Characteristics](#)
- [EC declaration of conformity](#)
- [Dimensional drawing](#)